

POWER ≠ PLEX[™] 40V MAX' LITHIUM ION PRODUCTS



TAKE CHARGE WITH TORO

BLOWER / CHAINSAW / HEDGE TRIMMER / STRING TRIMMERS

ypical usage. Actual voltage varies with load.



POWERFUL. DURABLE.

POWER + PLEX ** 40V MAX* LITHIUM ION



BATTERY ENERGYCOMPARED TO A GAS TANK**

VOLTS × AMP-HOURS **WATT-HOURS**

> SIZE OF GAS TANK **Total Energy**

BATTERY ENERGY CAN CHANGE BASED ON VOLTAGE OR AMP-HOUR CELL STRUCTURE

18V (20V Max) **36 WH** 36V (40V Max) **90WH** 2.5 AH 36V (40V Max) 5.0 AH **180WH** 18V (20V Max) 10.0 AH 180WH

> Designed for the future, PowerPlex battery housings will hold more fuel in the same tank.

When selecting a battery product, compare both competitive cost and watt-hours.

** Analogy for general battery information. Not for technical specifications.

A HIGHER WATT-HOUR WILL INCREASE RUNTIME ON THE SAME TOOL



60 min. charge time (Hedge Trimmer)

120 min. charge time (Hedge Trimmer)



RELATION OF SPEED TO RUNTIME



with variable speeds



QUICK CHARGER

- Fits Toro **POWER** # **PLEX** * tools
- Table top or wall mount option
- Charges T90 in 60 minutes, T180 in 120 Minutes



T90 BATTERY

- Fits Toro POWER # PLEX* tools
- 40-Volt max, 2.5 Amp-Hour,
- Comes standard with POWER # PLEX" tools
- On-board power meter



T180 BATTERY

- Fits Toro **POWER ? PLEX** tools
- 40-Volt max, 5.0 Amp-Hour, 180 Watt-Hour
- LED Flashlight lasts up to 60 min
- USB charging port for charging small devices • Folding handle makes carrying easier
- On-board power meter



BRUSHLESS DC BLOWER



MODEL 51134

Higher Speed = More Power

TURBO BOOST POWER WITH SPEED LOCKUp to 815 m³/h to move more faster

BRUSHLESS MOTOR More power, more runtime and longer life than brushed motor

ACCESSORY ATTACHMENT COLLAR & SPEED NOZZLE Increases air speed and fits Toro Gutter Cleaning Kit

VARIABLE SPEED Lower Speed = Longer Run Time

OPTIONAL ACCESSORIES: Gutter Cleaning Kit (51667)

36 CM BRUSHLESS DC CHAINSAW

MODEL 51138

BRUSHLESS MOTOR More power, more runtime and longer life than brushed motor

NO PULL EASY START Simply push the button

REDUCED KICKBACK Chain, bar tip indicator, chain

brake, and metal bucking teeth

AUTOMATIC CHAIN OIL With oil level indicator to know when to refill

TOOL-FREE CHAIN TENSIONING Adjust by turning knobs with fingers



61 CM HEDGE TRIMMER



MODEL 51136

61 CM HARDENED STEEL BLADESSturdy, thick and robust

90° ROTATING HANDLE Quick, easy vertical trimming

DUAL-ACTION CUTTING SYSTEM Reduces vibration

20% THICKER BLADE Than a Toro 20V hedge trimmer



33 CM STRING TRIMMER/EDGER

MODEL 51130

ADJUSTABLE LENGTH SHAFT Custom fit to operator height

0.2 CM THICK SINGLE LINE WITH AUTO FEED

Thicker, longer lasting line


TRIMMER TO EDGER One button push and twist between modes

VARIABLE SPEED Lower Speed = Longer Run Time Higher Speed = More Power



36 CM BRUSHLESS DC STRING TRIMMER

MODEL 51132



0.2 CM DUAL LINE WITH BUMP FEED Durable, productive line control

CAST-ALUMINUM HEAD For long-lasting durability

VARIABLE SPEED Lower Speed = Longer Run Time Higher Speed = More Power

STRAIGHT, FOLDABLE SHAFT For easy storage and transport







POWER & PLEX SPECIFICATIONS 40V MAX' LITHIUM ION PRODUCTS

	51134 BRUSHLESS BLOWER	51138 36 CM BRUSHLESS CHAINSAW	51136 61 CM HEDGE TRIMMER	51130 33 CM STRING TRIMMER/EDGER	51132 36 CM BRUSHLESS STRING TRIMMER
T90 BATTERY*					
Volts – Ah	40V - 2.5	40V - 2.5	40V - 2.5	40V - 2.5	40V - 2.5
Run time [^]	10-60 min	35-45 cuts/battery	60 min	45 min	40 min
Recharge (Quick Charger Included)	60 min	60 min	60 min	60 min	60 min
MOTOR	Brushless DC	Brushless DC	Brushless DC	Brushed DC	Brushless DC
SPEED (up to)	241 km/h 815 m³/h	11 m/s	3,200 SPM	N/A	N/A
CUTTING LENGTH	N/A	36 cm Bar	61 cm Bar	33 cm	36 cm
CUTTING TYPE	N/A	1 cm Pitch Chain	Dual action	Single .2 cm	Dual .2 cm
COMFORT	Variable Speed Cruise Control	Low-kickback Oregon Chain and Metal Bucking Teeth	90° Rotating Handle	Variable Speed Telescoping Shaft; Adjusting Assist Handle	Variable Speed Adjusting Assist Handle
WEIGHT	3.8 kg	5 kg	3.9 kg	3.8 kg	4.3 kg
WARRANTY	3-Year Full on Tools, 2-Year Full on Batteries				

Actual products may vary. All specifications to be verified with final product.



Count on it.

toro.com Worldwide Headquarters The Toro Company 8111 Lyndale Ave. So. Bloomington, MN 55420 U.S.A. Phone: (1) 952 888 8801 Fax: (1) 952 887 8258

©2017 The Toro Company. All Rights Reserved. Printed in the USA

200-XXXX

Products depicted in this literature are for demonstration purposes only. Actual products offered for sale may vary in use, design, required attachments and safety features. We reserve the right to improve our products and make changes in specifications, design and standard equipment without notice and without incurring obligation. See your distributor for details on all our warranties.









twitter.com/TheToroCompany

youtube.com/ToroCompanyEurope